

DESCRIPTION

MAGNETIC SPIRIT LEVEL 48 SPIRIT
MAGNET-RICHTWAAGE 48 SPIRIT

BESCHREIBUNG

SWISS MADE



Execution:

- **Standard version** with two prismatic measuring bases horizontal and vertical, vertical base with magnetic inserts, contact faces hand scraped for sensitivity 0.05 mm/m and better, manufactured and tested according to Standards DIN877 + DIN2276/1
- Simple adjustment of the zero-point and of rollover errors (twist) of the main vial, due to an ingenious adjusting system
- Excellent view on the vial from above and from the side
- The main vial being fixed in a special mounting device, the vial is absolutely free from any tensions
- Transversal vial with a sensitivity of 2-5 mm/m for easier handling of the level when measuring on horizontal shafts or in the vertical
- The prismatic base is suitable for shaft diameters Ø 19 ... Ø 108 mm
- A handle of precious wood eliminates the transfer and influence of the body temperature
- Packed in a wooden storage case

Function:

- The MAGNETIC SPIRIT LEVEL 48 SPIRIT is a universal spirit level, particularly suitable for measurements on vertical and horizontal surfaces and shafts

Twist stability according to WYLER standard:

- Rollover stability ±2 degrees

Weight:

| | |
|-----------------------------|----------|
| • Net weight (without case) | 1.500 kg |
| • Gross weight | 1.950 kg |

Two prismatic measuring bases, vertical base with magnetic inserts

Zwei prismatische Messbasen, vertikale Basis mit Magneteinsätzen

STANDARD-VERSION

Dimensions / Abmessungen:
 150 x 40 x 150 mm
 Shaft / Wellen
 Ø19 ... Ø108 mm

Two prismatic measuring bases, vertical and horizontal base with magnetic inserts

Zwei prismatische Messbasen, horizontale+vertikale Basis mit Magneteinsätzen

Dimensions / Abmessungen:
 150 x 40 x 150 mm
 Shaft / Wellen
 Ø19 ... Ø108 mm

| Sensitivity / Skalenteilungswert: | P/N Produktnummer | P/N Produktnummer |
|-----------------------------------|----------------------|----------------------|
| 0,02 mm/m | 148S150-247-020 | 148S150-248-020 |
| 0,05 mm/m | 148S150-247-050 | 148S150-248-050 |
| 0,10 mm/m | 148S150-247-100 | 148S150-248-100 |
| 0,30 mm/m | 148S150-247-300 | 148S150-248-300 |

| Calibration certificate | P/N | Produktnummer | Kalibrierzertifikat |
|---|----------|---------------|---|
| SCS calibration certificate for Magnetic Spirit Level 48 SPIRIT | SCS WW-W | | SCS-Kalibrierzertifikat für Magnet-Richtwaage 48 SPIRIT |