

DESCRIPTION

SCREW-ON SPIRIT LEVEL 66
AUFSCHRAUBBARE RICHTWAAGE 66

BESCHREIBUNG

SWISS  MADE

Execution:

- The vial of the SCREW-ON SPIRIT LEVEL 66 is firmly sealed in a stable steel body of cubic shape, outside gun-blued
- The SCREW-ON SPIRIT LEVEL 66, according to DIN877 + DIN2276/1, is available in various lengths and sensitivities (see table below)
- The SCREW-ON SPIRIT LEVEL 66 is equipped with 2 through holes for mounting on a measuring object
- Without case

Function:

- The SCREW-ON SPIRIT LEVEL 66 is specially designed for measurements on flat surfaces of machines, apparatus, etc. as well as for permanent mounting on measuring objects

Ausführung:

- Die Libelle der AUFSCHRAUBBAREN-RICHTWAAGE 66 ist in ein stabiles, brüniertes Vierkant-Stahlprofil eingegossen
- Die AUFSCHRAUBBARE-RICHTWAAGE 66 nach DIN877 + DIN2276/1 ist in verschiedenen Abmessungen und Skalenteilungswerten lieferbar (siehe nachstehende Tabelle)
- Die AUFSCHRAUBBARE-RICHTWAAGE 66 ist mit Bohrungen zum Aufschrauben der Richtwaage versehen (siehe nachstehende Tabelle)
- Ohne Holzetui

Funktion:

- Die AUFSCHRAUBBARE-RICHTWAAGE 66 eignet sich hervorragend für das Messen von Flächen an Maschinen, Apparate, usw. sowie für die permanente Installation an Messobjekten

Sensitivity / Skalenteilungswert:	P/N Produktnummer	Dimensions / Abmessungen	Weight/ Gewicht	Hole center distance / Lochabstand	Screws / Schraube
2-5 mm/m	166-030-121,002	30 x 10 x 10 mm	0.015 kg	25 mm	M2
2-5 mm/m	166-040-121,002	40 x 10 x 11 mm	0.025 kg	35 mm	M2
1.0 mm/m	166-050-121,001	50 x 10 x 12 mm	0.030 kg	40 mm	M2
2-5 mm/m	166-050-121,002				
0.30 mm/m	166-060-121-300	60 x 12 x 14 mm	0.050 kg	50 mm	M3
1.0 mm/m	166-060-121,001				
2-5 mm/m	166-060-121,002				
0.10 mm/m	166-080-121-100	80 x 15 x 18 mm	0.100 kg	70 mm	M4
0.30 mm/m	166-080-121-300				
1.0 mm/m	166-080-121,001				
0.10 mm/m	166-100-121-100	100 x 18 x 22 mm	0.200 kg	86 mm	M4
0.30 mm/m	166-100-121-300				
1.0 mm/m	166-100-121,001				
0.10 mm/m	166-120-121-100	120 x 18 x 22 mm	0.250 kg	105 mm	M4
0.30 mm/m	166-120-121-300				
1.0 mm/m	166-120-121,001				
0.10 mm/m	166-150-121-100	150 x 18 x 22 mm	0.300 kg	135 mm	M4
0.30 mm/m	166-150-121-300				
1.0 mm/m	166-150-121,001				

Calibration certificate	P/N	 Produktnummer	Kalibrierzertifikat
SCS calibration certificate for Screw-on Spirit Level 66		SCS WW-H	SCS-Kalibrierzertifikat für Aufschraub-Richtwaage 66